


MALE RUN TEES



SPECIFICATIONS

Tube O.D.	Pipe Thd.	Thread	A	B	D +.005/ .010	E	F	G	H	K	M
			± 1/64	± 1/64			± .010	± 1/64	± 1/64	± 1/64	± 1/64
1/4	1/8	7/16-20	1-15/32	3/4	.250	.330 - .335	.170	15/32	47/64	3/8	23/64
1/4	1/4	7/16-20	1-21/32	15/16	.250	.330 - .335	.170	15/32	47/64	3/8	3/8
5/16	1/4	1/2-20	1-3/16	1-1/64	.312	.380 - .385	.232	31/64	13/16	7/16	7/16
3/8	1/4	5/8-20	2	1-3/64	.375	.460 - .465	.250	19/32	31/32	35/64	35/64
3/8	3/8	5/8-20	2-1/8	1-3/32	.375	.460 - .465	.250	19/32	31/32	37/64	37/64
1/2	3/8	3/4-20	2-1/4	1-9/64	.500	.590 - .595	.375	11/16	1-7/64	11/16	11/16
1/2	1/2	3/4-20	2-3/8	1-9/32	.500	.590 - .595	.375	11/16	1-3/32	21/32	43/64
5/8	1/2	7/8-20	2-47/64	1-15/32	.625	.715 - .720	.500	45/64	1-1/4	13/16	13/16
3/4	1/2	1-1/16-20	3-3/16	1-39/64	.750	.860 - .865	.625	13/16	1-37/64	1	1-3/64
3/4	3/4	1-1/16-20	3-3/16	1-5/8	.750	.860 - .865	.625	13/16	1-9/16	1	1-3/64
7/8	3/4	1-3/16-16	3-3/16	1-5/8	.875	.995 - 1.000	.750	7/8	1-9/16	1-1/8	1-3/16