



More than just pumps



## Flow Meter FMT 50 PP



# FLUX Flow Meter Type FMT 50 PP



The cost effective interlocked wheel impeller in the measuring chamber guarantees a fast and safe filling process. Suitable for neutral, low viscosity, not flammable liquids in conjunction with our JUNIORFLUX pump.

#### Benefits:

User-friendly handling, 5-digit LCD-Display, indication of the subset and total (not resetable), fast and safe calibration.

Type	FMT 50 PP
Flowrate	5-50 l/min
Operating pressure at 20 °C	4 bar
Viscosity	max. 40 mPas (cP)
Operating temperature	- 10 °C up to max. + 50°C
Accuracy (not calibrated)	± 2 %
Accuracy (calibrated)	± 1 %
Inlet-outlet connections	Inlet G 1 (BSP 1"), outlet G 1A (BSP 1" male)
Material: housing	Polypropylene (PP)
Material: seal	FKM
Protection	IP 65
Weight	0,3 kg
Part No.	A05 00 003

Please ask for more information on FLUX liquid meters and details on our laboratory and barrel pump JUNIORFLUX. We would be glad to send you a detailed catalogue.



More than just pumps

**FLUX-GERÄTE GMBH**  
 Talweg 12 · D-75433 Maulbronn  
 Tel. 07043 101-440 · Fax 07043 101-444  
 Fax International +49 7043 101-555  
 info@flux-pumpen.de · www.flux-pumpen.de