




DCD P 600 N

Double-Clip Machine



innovative · reliable · leading



- Netted packaging for fruit, vegetable, bulk products and similar
- Suitable as final packaging for metal detection
- Plastic clips on spools
- Extremely easy handling

Applications

The DCD P 600 N double-clip machine securely closes all nets. The pneumatic machine is also ideal for installation in secured packaging units.

Clip-Version P 600 N

The clip-version P 600 N is a special designed and patented plastic clip formed like a trident. Its shape ensures that it pins particularly reliably to all nets. The clip cannot be pulled off the net.

Advantages

- Fatigue-free product supply and operation
- Free view of the working area
- Separator absolutely gentle to the netting
- Also suitable for fixing flags and price tags
- Pneumatic pressure control guarantees gentle net closure
- High performance at a low price
- Automatic cut-off knife
- Processes high-quality plastic clips – certified safe for use with food by SGS INSTITUT FRESENIUS, tested according to FDA
- Clip and loop manufacture certified in accordance with ISO 22000:2005, which incorporates HACCP requirements
- Hygienic:
 - made completely of stainless steel and robust industrial plastic
 - smooth surfaces make it easy to clean
 - no external screws



Patented plastic clip for secure closure of netting with DCD P 600 N

- Secure stand
- Extremely easy maintenance

Optional equipment

- Version with automatic separator for installation in secured units
- Pressure reducer with filter

Function and operation

The DCD P 600 N operates pneumatically. By closing the ergonomically shaped separator gate the end of the net and the start of the next packaging unit are securely closed. At the same time, the net can be cut through between the two clips by the press of a button.

The DCD P 600 N securely closes netted packaging for fruit, vegetable, bulk products and the like.



Technical Data

Width:	240 mm
Length:	520 mm
Height:	950 mm
Weight:	27 kg
Compressed air:	5-6 bar/0.5-0.6 MPa
Air consumption:	4.6 NL/cycle

Suitable clip sizes:
 DCD P 600: P 628, P 632
 DCD P 600 N: P 628 N, P 632 N