

EZ P 600/700

Single-Clip Machine



CLIP LINE
Easy



innovative · reliable · leading

poly-clip[®]
SYSTEM

- For closure of bags and nets
- Easy metal detection
- Plastic clips in different colours
- Firm, safe packaging

Application

The clipping machines EZ P 600/700 of the Easy Clip Line® are the safe way to package poultry, bakery products, fruits, vegetables and many others in bags or nets. The nonmetal clip allows for an easy metal detection of the finished product. These plastic clips are available in different sizes and colours, and are furnished on spools.

Advantages

- Patented clip shape with precise guidance of the clip
- Clips on spools
- Firm, uniform closure every time
- Automatic clip triggering by insertion of the tail into the slot of the clip guide
- Quick and simple operation
- Integrated pneumatic knife for shortening the bag tail
- Table top or in-built version, left-hand or right-hand, with backward-inclined or upright machine on base plate



- Low air consumption
- Low maintenance and low wear owing to the small number of moving parts
- Coded plastic clips P 600 for product identification factory-provided
- Hygienic design made of stainless steel and industrial plastic for easy cleaning
- Processes high-quality plastic clips – certified safe for use with food by SGS INSTITUT FRESENIUS, tested according to FDA
- Clip and loop manufacture certified in accordance with ISO 22000:2005, which incorporates HACCP requirements
- Can be combined with the MPL poultry loader (bagger)

the clip guide, the tail is shirred and the clipping process is triggered automatically. In parallel, the bag tail is cut with the pneumatic knife.

Technical Data

| | |
|----------------------|---------------------|
| Width: | 311 mm |
| Depth: | 467 mm |
| Height: | 758 mm |
| Weight: | 15 kg |
| Compressed air: | 5-7 bar/0.5-0.7 MPa |
| Air consumption | |
| 5 bar: | 2.4 NL/cycle |
| 7 bar: | 2.7 NL/cycle |
| Suitable clip sizes: | |
| | P 632/638 |
| | P 744 |



Optional equipment

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod at diameters of 35-48 mm
- Pressure reducer with filter
- Machine feet (table top version)
- Labelling system EZ Tag-Feeder for tamper-proof product and origin labelling, as well as batch tracing

Function and operation

The clipping machines EZ P 600/700 operate pneumatically. By inserting the tail into the slot of

Poly-clip System GmbH & Co. KG
 Niedeckerstraße 1 · 65795 Hattersheim a. M.
 Germany · Tel. +49 6190 8886-0
 contact@polyclip.de · www.polyclip.com