

Liquid Filled Stainless Case Gauges

Features:

- PowerFlex™ movement with polyester segment designed to resist the effects of shock, vibration and pulsation.
- ASME B40.100, Grade B (\pm 3-2-3% accuracy)
- copper alloy bourdon tube
- white aluminum dial with black numbers and black aluminum pointer
- 1/4" NPT brass connection
- glycerin filled
- polycarbonate window
- temperature range: -4°F to 140°F

2 1/2" face
1/4" center back mount



GLSC420

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	GLSC400	\$56.20
0-30	5	.5	GLSC405	56.20
0-60	10	1	GLSC410	56.20
0-100	20	2	GLSC415	56.20
0-160	20	2	GLSC417	56.20
0-200	50	5	GLSC420	56.20
0-300	50	5	GLSC425	56.20
0-400	100	10	GLSC427	56.20
0-600	100	10	GLSC430	56.20
0-1000	200	20	GLSC435	56.20
0-1500	300	20	GLSC440	62.10
0-2000	500	50	GLSC445	62.10
0-3000	500	50	GLSC450	62.10
0-5000	1000	100	GLSC455	62.10

2 1/2" face
1/4" lower mount



GLS430

PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	GLS400	\$45.50
0-30	5	.5	GLS405	45.50
0-60	10	1	GLS410	45.50
0-100	20	2	GLS415	45.50
0-160	20	2	GLS417	45.50
0-200	50	5	GLS420	45.50
0-300	50	5	GLS425	45.50
0-400	100	10	GLS427	45.50
0-600	100	10	GLS430	45.50
0-1000	200	20	GLS435	45.50
0-1500	300	20	GLS440	50.90
0-2000	500	50	GLS445	50.90
0-3000	500	50	GLS450	50.90
0-5000	1000	100	GLS455	50.90

Liquid Filled ABS Case Gauges

Feature:

- ASME B40.100, Grade B (\pm 3-2-3% accuracy)

2 1/2" face
1/4" lower mount



PSI Range	Fig. Inter.	Minor Grad.	Part #	Price/E
0-15	3	.2	GLP500	\$35.25
0-30	5	.5	GLP505	35.25
0-60	10	1	GLP510	35.25
0-100	20	2	GLP515	35.25
0-160	20	2	GLP517	35.25
0-200	50	5	GLP520	35.25
0-300	50	5	GLP525	35.25
0-400	100	10	GLP527	35.25
0-600	100	10	GLP530	35.25
0-1000	200	20	GLP535	40.10
0-1500	300	20	GLP540	40.10
0-2000	500	50	GLP545	40.10
0-3000	500	50	GLP550	40.10
0-5000	1000	100	GLP555	40.10