

STERLING

## MH SERIES Machine Hopper

# **Technical Specifications**

MH Series machine hopper loaders offer a unique mass flow and compact design. MH machine hoppers are available in insulated and non-insulated configurations and larger models also include a hinged access door for easy access and maintenance.

### Features

#### **Standard Features**

- Compact design
- Hinged access door available on 3.0 cu. ft. models and larger sizes
- Slide gate
- Stainless steel construction
- Insulated construction on 0.85 and 1.7 cu. ft. models
- Easy-view Lexan® sight glass
- Adjustable quick-release clamp design
- Cover selections available for mounting various loaders configurations
- 7" x 7" square flange

#### **Optional Features**

- Premium machine-mount slide gate
- Flange transition from 7" to 4" square
- Drawer magnet with slide gate
- Blank cover
- Manual fill cover
- Vacuum hopper cover





Dimensions

Model	MHx.x						
	0.85	1.7	1.7 with door	3.0	6.0		
Capacity (cu.ft/l)	0.85/25	1.7/50	1.7/50	3.0/85	6.0/170		
Square Flange	7″ x 7″ (178 mm x 178 mm)						
Insulated diameter. in. (mm)	14 (356)		16 (406)	22 (559)			

## Specifications

Model	Recommended Vacuum Hopper size (lbs)	Recommended Vacuum Power Unit size (hp)	Material and Vacuum tube size, in.	Height, In. (mm)	Diameter, In. (mm)	Shipping weight (with vacuum receiver), lbs. (kg)
3/5	25	3.5	1.5	16 (406)	8 (203)	35 (16)
	50	3.5				
	100	5	2			
7.5/10	50	7.5	2.5	24 (610)	10 (254)	40 (18)
	100	7.5/10	25/20			
	200	10	2.5/3.0			
15	100	15	3/3.5	30 (762)	10 (254)	50 (23)
	200					
25	200	25	4 Sch. 10	36 (914)	12 (305)	75 (34)
30	200	30	5 Sch. 10	44 (1118)	16 (406)	75 (34)

Vacuum receiver and vacuum pump sold separately.

