

# WITT-SWITCH

## Control Unit for pressure regulating stations



**Switch and Control Unit for automatic change over of pressure regulating stations. Provides a smooth process flow and optimal results with a continuous gas flow.**

### Benefits

- intelligent control, - the last selected gas supply will be activated after an emergency stop
- freely selectable side for starting
- compatible with WITT-Pressure regulating station
- quick and easy wall mounting
- optimal draw down of cylinder
- audible and visual alarm
- status indication by illuminated push-button and display
- integrated emergency cut-out

### Operation / Usage

- for automatic change over of pressure regulating stations for continuous gas withdrawal
- applicable for switching an emergency supply

### Function

- automatic change over with controlled limit values by two solenoid valves between two connected cylinders or cylinder bundles

### Options

- additional audible alarm device
- flashing beacon

### Approvals

Company certified according to ISO 9001

Technical Data	
Order-No.	194-019
Voltage	230 V AC, 24 V DC
Power consumption	0.4 A
Housing	polycarbonate (plastic material)
Enclosure rating	IP65
<b>Dimensions</b>	
Height	approx. 310 mm (12.20 inch)
Width	approx. 330 mm (12.99 inch)
Depth	approx. 175 mm (6.89 inch)
<b>Weight</b>	approx. 3.0 kg