

<b>THE MALT</b>	<b>BEST Pale Ale</b> deepens the light "golden" color of top-fermented beers, creating a pleasant flavor. It forms an excellent enzyme-rich foundation for intensive colored beer styles. It is an excellent base malt for brewing many different styles of British pale ale as well as for brewing Kölsch beer.
<b>USE</b>	For pale ale, Kölsch and more beers
<b>RATE</b>	100 % of the grainbill
<b>PACKAGING</b>	In bulk, sacks size 25 kg/55 lbs and 50 kg/110 lbs, super sacks size 500-1,000 kg/1,100-2,200 lbs
<b>SHELF LIFE</b>	At least 24 months under dry conditions (max. 20 °C/68 °F, max. 35 % RH).
<b>SERVICE</b>	Should you need personal assistance, one of our experts will be happy to advise you. Please do not hesitate to contact us with any questions. Or find more information on our website at <a href="http://www.bestmalz.com">www.bestmalz.com</a> .
<b>REMARKS</b>	<p>All of our malts are produced in accordance with the purity guidelines of the German Reinheitsgebot of 1516. We use no genetically modified raw materials. Our malts are produced in compliance with all valid food regulations and legal provisions. Of course, absolute compliance with strict statutory limits relating to pesticides, herbicides, fungicides, mycotoxins and nitrosamines is guaranteed. This is checked by independent laboratories on a regular basis.</p> <p>All processes are conducted according to procedures that are stipulated in our quality management system in accordance with the European standard DIN-EN-ISO 9001:2008. This also comprises a HACCP system. Certification of the systems is performed regularly by the LGA InterCert.</p> <p>Malting barley and wheat are natural products. This means that the specifications given here are subject to seasonal variation and are based on a minimum level of quality for the harvested grain. Please find more information on our website at <a href="http://www.bestmalz.com">www.bestmalz.com</a>.</p>

**STANDARD MALT SPECIFICATIONS** (the values are harvest dependant)

Specification	Unit	Minimum	Maximum
Moisture content	%		5,0
Extract fine grind, dry basis	%	80,5	
Fine-coarse difference EBC	%		2,0
Viscosity (8,6%)	mPa·s		1,60
Friability	%	80,0	
Glassiness	%		3,0
Protein, dry basis	%	9,0	11,5
Soluble nitrogen	mg/100g	610	780
Kolbach index	%	36,0	45,0
<b>Wort color</b>	<b>EBC</b>	<b>5,0</b>	<b>7,0</b>
<b>Wort color</b>	<b>L</b>	<b>2,3</b>	<b>3,1</b>
Wort pH		5,70	6,10
Grading > 2,5mm	%	90,0	
Diastatic power	WK	250	



BESTMALZ AG • P.O. BOX 10 43 20 • D-69033 HEIDELBERG • GERMANY

T +49 (0)62 21 - 64 66-0 • F +49 (0)62 21 - 64 66-99 • INFO@BESTMALZ.DE • WWW.BESTMALZ.COM